

The Torx-system gives maximum contact area for male and female heads. Faster assembly, lower tool costs and undamaged surfaces on the attachment and other parts.



Internal six point slot according to the Torx-system



External six point slot according to the Torx-system



Spanner No	Key size (Slot) A mm	For metric screw *)	For imperial thread screw	Spanner No	Key size (Slot) A mm	For metric screw *)
TX 5	1,42	M 1.6	–	–	–	–
TX 6	1,70	M 2	–	–	–	–
TX 7	1,99	M 2.5	–	–	–	–
TX 8	2,31	M 2.5	–	–	–	–
TX 9	2,50	M 3	–	E 4	3,86	M 3
TX 10	2,74	M 3 – M 3.5	ST 2.9 – ST 3.5	–	–	–
TX 15	3,27	M 3.5 – M 4	–	–	–	–
TX 20	3,86	M 4 – M 5	ST 4.2	E 5	4,75	M 4
TX 25	4,43	M 4.5 – M 5	ST 4.8 – ST 5.5	E 6	5,74	M 5
TX 27	4,99	M 4.5 – M 6	–	E 7	6,78	M 6
TX 30	5,52	M 6 – M 7	ST 6.3	E 8	7,52	M 6 – M 7
TX 40	6,65	M 7 – M 8	–	–	–	–
TX 45	7,82	M 8 – M 10	–	E 10	9,42	M 8
TX 50	8,83	M 10	–	E 12	11,70	M 10
TX 55	11,25	M 12	–	E 14	12,90	M 12
–	–	–	–	E 16	14,76	M 12
TX 60	13,25	M 14	–	E 18	16,70	M 14
–	–	–	–	E 20	18,39	M 16

*) Varies between manufacturers. **Bold indicates the most common.**